

Terminal Tractor/Yard Spotter

Used Yard Spotter Gresham - Tow tractors are a common piece of industrial equipment used in large buildings, arenas, warehouses, airports and manufacturing plants for moving loads horizontally. They go by different names including tow tugs and towing tractors. They are capable of towing several trailers in a train formation. Tow tractors can move aircraft into and outside of airport locations such as terminals and hangars. All tow tractors use the concept of tractive effort to move loads. Tractive effort refers to the total amount of traction a vehicle deploys on the ground. Heavier loads require more tractive effort compared to lighter loads. The tow tractor lifts a portion of the load during towing while ensuring the wheels on the load still remain on the ground. The load is partially lifted by use of the tow tractor's hydraulic mast which is specifically designed to produce downforce on the drive wheel immediately beneath it, increasing the tractive effort. Traction allows the machine to deliver very large and heavy loads.

Types of Tow Tractors There are two basic types of tow tractors: 1. Load carriers; and 2. Heavy-duty tow tractors; Load Carriers Many industries including airport baggage divisions, manufacturing, parcel transportation and e-commerce rely on moving items of various sizes to and from different locations. Load carrier tow tractors or tow tugs are especially useful for these types of applications because they allow the single items to be gathered and stacked on the wheeled platforms, ready to be attached for tow and transport by the tow tractor. Load carrier tow tractor models are categorized in the material handling equipment that covers cranes, forklifts and pallet jacks. Load carrier tow tugs do not transport items from high places such as shelves or platforms. They only move cargo at ground level. This means that the load has already been on wheels or placed on a wheeled platform before transport. Wheeled platforms are called skates, trollies and bogies. The tow tug is attached to the trolley similar to train cars being attached to a locomotive. Generally, the steel coupling on the tow tug's male-end joins to the front trolley's female-end. The trolley's back portion has a male-end steel coupling that can be used to connect a variety of trollies to a single tug. These machines can transport a variety of items in varying conditions. The availability of many different types of trollies also allows for greater customization in transporting items. Many trollies can be connected since they are compatible with one another. This means several different types of trollies can be used in a single train allowing greater flexibility for operations. Load carrier tow tractors deliver a clear view for the operator which can be better than relying on forklifts. Further, load carrier tow tractors tow their trollies behind them in a forward-only direction which decreases the safety concerns created by forklifts operating in reverse. These safety considerations are of special importance in busy areas such as manufacturing floors and airports. Towing solutions are a good alternative to traditional forklifts to handle many single items. They are safe and easy to maneuver. The operator doesn't require a license, which is another benefit compared to forklifts. Tow tractor operators do not need licenses since they don't lift loads off of the ground. Three subtypes of load carrier tow tractors include rider-seated, stand-in and pedestrian.

Pedestrian Tow Tractors A walk-behind model that can transport wheeled loads is called a pedestrian tow tractor. These machines may go by the names of electric hand tug, electric tugger, electric tug or tow tractor. These machines are simple to use, extremely maneuverable and very compact.

Stand-in Tow Tractors Popular for industries that conduct order picking and horizontal transport for manufacturing, the stand-in tow tractors are the best design. They provide a secure platform for the driver to operate while still having a smaller footprint than that of the rider-seated tow tractors.

Rider-Seated Tow Tractors Rider-seated tow tractors are similar to stand-in models except they offer a seated platform for the operator. These types of load carrier tow tractors are popular where loads are transported over longer distances, such as airport baggage systems where checked baggage is transported from the check-in counter at the front of an airport to the aircraft at the terminal, often a great distance from one another. Rider fatigue is decreased with sit-down units for more efficiency and productivity.

Heavy Duty Tow Tractors Aviation relies on the pushback concept for moving big passenger and cargo aircraft. Pushback refers to the process of pushing an aircraft

back from an airport terminal by some means other than the aircraft's own power. Heavy-duty tow tractors are known as pushback tugs or pushback tractors complete this task. Pushback tugs feature a low-profile enabling them to travel under the aircraft's nose for easy attachment. Since the aircraft weight is heavy, these units need to be heavy in order to retain adequate ground friction to move the aircraft. A common tractor for moving large aircraft can weigh in up to fifty-four tons. Their driver's cab has the ability to be lowered and raised for increased visibility during reversing. The unit is called a pushback tow tractor or pushback tug but it is additionally used to move aircraft in situations where taxiing is not safe or practical including into and outside of aircraft maintenance. The pushback tow tractors come in two subtypes, the towbarless and the conventional. Conventional Pushback Tow Tractors These units use a tow bar to attach the tug to the nose landing gear on the aircraft. The tow bar is fixed laterally at the nose landing gear, but may move slightly vertically for height adjustment. At the end that attaches to the tug, the tow bar may pivot freely laterally and vertically. The tow bar functions as a sizeable lever to facilitate nose landing gear rotation. Every aircraft has a special tow fitting and the towbar functions as an adapter between the fitting on the landing gear and the standard-sized tow pin. Heavy-duty towbars required for sizeable aircraft ride on their own wheels when they are disconnected from the machine. The wheels are attached to a hydraulic jacking mechanism which can lift the towbar to the correct height to mate to both the airplane and the tug, and once this is accomplished the same mechanism is used in reverse to raise the tow bar wheels from the ground during the pushback process. The towbar can be connected at the front or the rear of the tractor, depending on whether the aircraft will be pushed or pulled. Towbarless Pushback Tow Tractors Towbarless tractors do not use a towbar; they scoop up the nose landing gear and lift it off the ground, allowing the tug to maneuver the aircraft. This allows better control of the aircraft and higher speeds; it may also eliminate the need to have a worker in the cockpit to apply the aircraft's brakes. The main advantage of a towbarless tug is simplicity; there is no need to maintain multiple towbars. Greater control and responsiveness while moving the aircraft is achieved with this direct connection of the tug to the landing gear.